

NEW CARTRIDGE NEEDLE PACKING

ANEST IWATA Century Series Spray Guns install
New Cartridge Needle Packing

Features:

- * Longer life
- * Self tensioning
- * Suitability for any type of solventborne and waterborne paint

Replacement Packing: W101: Part# 93765610

W200: Part# 93810620

W400: Part# 93810620

Repair Service Kit: Part# W101.RSK

W200.RSK

W400.RSK

How to install:

1. Make sure that there is no paint residue or dust on the threads and seat surface of Gun Body. Clean the Gun Body if needed.
2. Apply gun lube inside Cartridge Needle Packing.
3. Hand tighten the Cartridge Needle Packing on the Gun Body and insert Fluid Needle from Fluid Adj. Set. If it is difficult to insert the Fluid Needle into the Cartridge Needle Packing, twist the Fluid Needle during insertion.
4. Tighten the Cartridge Needle Packing 15-60 degrees (5-20 minutes) by using ANEST IWATA Gun Wrench.
5. Pull and release the Trigger couple times and make sure the Fluid Needle moves back and forth smoothly. If not, the Cartridge Needle Packing is too tight. Loosen it and repeat steps 3 to 5.

Important:

* If you tighten the fluid needle packing set too much, fluid needle will not move smoothly and may not return to fully closed position, resulting in paint leakage from the tip of the fluid nozzle. Try to adjust it carefully while pulling trigger and confirming movement of fluid needle set. If you tighten it too much, first fully loosen it and then tighten it again carefully.

* Cartridge Needle Packing is supplied as set and individual parts of Cartridge Needle Packing are not available separately.

